
geography3

Aug 11, 2021

Contents:

1	geography package	1
1.1	Submodules	1
1.2	geography.extraction module	1
1.3	geography.labels module	1
1.4	geography.locator module	2
1.5	geography.places module	10
1.6	geography.prefixtree module	10
1.7	geography.utils module	10
1.8	geography.wikidata module	10
1.9	Module contents	12
2	setup module	13
3	tests package	15
3.1	Submodules	15
3.2	tests.test_extractor module	15
3.3	tests.test_locator module	16
3.4	tests.test_places module	17
3.5	tests.test_prefixtree module	18
3.6	tests.test_wikidata module	18
3.7	Module contents	18
4	Indices and tables	19
	Python Module Index	21
	Index	23

CHAPTER 1

geography package

1.1 Submodules

1.2 geography.extraction module

```
class geography.extraction.Extractor (text=None, url=None, debug=False)
Bases: object

Extract geo context for text or from url

find_entities (labels=['GPE', 'GSP', 'PERSON', 'ORGANIZATION'])
    Find entities with the given labels set self.places and returns it :param labels: Labels: The labels to filter
        Returns List of places
        Return type list

find_geoEntities ()
    Find geographic entities
        Returns List of places
        Return type list

set_text ()
    Setter for text

split (delimiter=',')
    simpler regular expression splitter with no entity check
    hat tip: https://stackoverflow.com/a/1059601/1497139
```

1.3 geography.labels module

Created on 2020-09-10

```
@author: wf

class geography.labels.Labels
    Bases: object

    NLTK labels

    default = ['GPE', 'GSP', 'PERSON', 'ORGANIZATION']

    geo = ['GPE', 'GSP']
```

1.4 geography.locator module

The locator module allows to get detailed city information including the region and country of a city from a location string.

Examples for location strings are:

Amsterdam, Netherlands Vienna, Austria Vienna, IL Paris - Texas Paris TX

the locator will lookup the cities and try to disambiguate the result based on the country or region information found.

The results in string representationa are:

```
Amsterdam (NH(North Holland) - NL(Netherlands)) Vienna (9(Vienna) - AT(Austria)) Vienna
(IL(Illinois) - US(United States)) Paris (TX(Texas) - US(United States)) Paris (TX(Texas) - US(United
States))
```

Each city returned has a city.region and city.country attribute with the details of the city.

Created on 2020-09-18

@author: wf

```
class geography.locator.City(**kwargs)
    Bases: geography.locator.Location

    a single city as an object

    country

    static fromGeoLite2(record)

    classmethod getSamples()

    region

    setValue(name, record)
        set a field value with the given name to the given record dicts corresponding entry or none
```

Parameters

- **name** (*string*) – the name of the field
- **record** (*dict*) – the dict to get the value from

```
class geography.locator.CityManager(name: str = 'CityManager', primaryKey: str = None, config=None, handleInvalidListTypes=False, filterInvalidListTypes=False, debug=False)
```

Bases: geography.locator.LocationManager

a list of cities

```
classmethod fromJSONBackup(config: lodstorage.storageconfig.StorageConfig = None)
    get city list from json backup (json backup is based on wikidata query results)
```

Parameters `jsonStr (str)` – JSON string the CityList should be loaded from. If None json backup is loaded. Default is None

Returns CityList based on the json backup

```
classmethod fromWikidata (fromBackup: bool = True, countryIDs: list = None, regionIDs: list = None, config: lodstorage.storageconfig.StorageConfig = None)
```

get city list form wikidata

Parameters

- `fromBackup (bool)` – If True instead of querying wikidata a backup of the wikidata results is used to create the city list. Otherwise wikidata is queried for the city data. Default is True
- `countryIDs (list)` – List of countryWikiDataIDs. Limits the returned cities to the given countries
- `regionIDs (list)` – List of regionWikiDataIDs. Limits the returned cities to the given regions

Returns CityList based wikidata query results

```
classmethod getLocationLodFromJsonBackup ()
```

```
updateCity (wikidataid: str, cityRecord: dict)
```

Updates the city corresponding to the given city with the given data. If the city does not exist a new city object is created and added to this CityList :param wikidataid: wikidata id of the city that should be updated/added :type wikidataid: str :param cityRecord: data of the given city that should be updated/added :type cityRecord: dict

Returns Nothing

```
class geography.locator.Country (lookupSource='sqlDB', **kwargs)
```

Bases: `geography.locator.Location`

a country

```
static fromGeoLite2 (record)
```

create a country from a geolite2 record

```
static fromPyCountry (pcountry)
```

Parameters `pcountry (PyCountry)` – a country as gotten from pycountry

Returns the country

Return type `Country`

```
classmethod getSamples ()
```

```
class geography.locator.CountryManager (name: str = 'CountryManager', primaryKey: str = None, config=None, handleInvalidListTypes=False, filterInvalidListTypes=False, debug=False)
```

Bases: `geography.locator.LocationManager`

a list of countries

```
classmethod fromErdem ()
```

get country list provided by Erdem Ozkol <https://github.com/erdem>

```
classmethod fromJSONBackup (config: lodstorage.storageconfig.StorageConfig = None)
```

get country list from json backup (json backup is based on wikidata query results)

Returns CountryList based on the json backup

```
classmethod fromWikidata()
    get country list form wikidata

classmethod from_sqlDb (sqlDB)

classmethod getLocationLodFromJsonBackup ()

class geography.locator.Earth
    Bases: object

    radius = 6371.0

class geography.locator.Location (**kwargs)
    Bases: lodstorage.jsonable.JSONAble

    Represents a Location

    balltreeQueryResultToLocationManager (distances, indices, lookupListOfLocations)
        convert the given ballTree Query Result to a LocationManager

        Parameters
            • distances (list) – array of distances
            • indices (list) – array of indices
            • lookupListOfLocations (list) – a list of valid locations to use for lookup

        Returns a list of result Location/distance tuples

        Return type list

    distance (other) → float
        calculate the distance to another Location

        Parameters other (Location) – the other location
        Returns the haversine distance in km

    getLocationsWithinRadius (lookupLocationManager, radiusKm: float)
        Gives the n closest locations to me from the given lookupListOfLocations

        Parameters
            • lookupLocationManager (LocationManager) – a LocationManager object to
                use for lookup
            • radiusKm (float) – the radius in which to check (in km)

        Returns a list of result Location/distance tuples

        Return type list

    getNClosestLocations (lookupLocationManager, n: int)
        Gives a list of up to n locations which have the shortest distance to me as calculated from the given
        listOfLocations

        Parameters
            • lookupLocationManager (LocationManager) – a LocationManager object to
                use for lookup
            • n (int) – the maximum number of closest locations to return

        Returns a list of result Location/distance tuples

        Return type list
```

```

classmethod getSamples()

static haversine(lon1, lat1, lon2, lat2)
    Calculate the great circle distance between two points on the earth (specified in decimal degrees)

isKnownAs(name) → bool
    Checks if this location is known under the given name

        Parameters name (str) – name the location should be checked against

        Returns True if the given name is either the name of the location or present in the labels of the
            location

class geography.locator.LocationContext(countryManager: geography.locator.CountryManager, regionManager: geography.locator.RegionManager, cityManager: geography.locator.CityManager)
    Bases: object
    Holds LocationManagers of all hierarchy levels and provides methods to traverse through the levels

cities

countries

classmethod fromCache(config: lodstorage.storageconfig.StorageConfig = None, forceUpdate: bool = False)
    Inits a LocationContext form Cache if existent otherwise init cache

classmethod fromJSONBackup(config: lodstorage.storageconfig.StorageConfig = None)
    Inits a LocationContext form the JSON backup

getCities(name: str)
    Returns all cities that are known under the given name

getCountries(name: str)
    Returns all countries that are known under the given name

static getDefaultConfig() → lodstorage.storageconfig.StorageConfig
    Returns default StorageConfig

getRegions(name: str)
    Returns all regions that are known under the given name

interlinkLocations()
    Interlinks locations by adding the hierarchy references to the locations

locateLocation(*locations)
    Get possible locations for the given location names. Current prioritization of the results is city(ordered by
    population)→region→country ToDo: Extend the ranking of the results e.g. matching of multiple location
    parts increase ranking :param *locations:

    Returns:

regions

class geography.locator.LocationManager(name, entityName, entityPluralName: str, listName: str = None, clazz=None, primaryKey: str = None, config=None, handleInvalidListTypes=False, filterInvalidListTypes=False, debug=False)
    Bases: lodstorage.entity.EntityManager
    a list of locations

```

static downloadBackupFile (url: str, fileName: str, force: bool = False)

Downloads from the given url the zip-file and extracts the file corresponding to the given fileName.

Parameters

- **url** – url linking to a downloadable gzip file
- **fileName** – Name of the file that should be extracted from gzip file
- **force (bool)** – True if the download should be forced

Returns Name of the extracted file with path to the backup directory

static getBackupDirectory ()

getBallTuple (cache: bool = True)

get the BallTuple=BallTree,validList of this location list

Parameters

- **cache (bool)** – if True calculate and use a cached version otherwise recalculate on
- **call of this function (every)** –

Returns a sklearn.neighbors.BallTree for the given list of locations, list: the valid list of locations list: valid list of locations

Return type BallTree,list

getByName (name: str)

Get locations matching given name :param name: Name of the location

Returns Returns locations that match the given name

static getFileContent (path: str)

getLocationByID (wikidataID: str)

Returns the location object that corresponds to the given location

Parameters **wikidataID** – wikidataid of the location that should be returned

Returns Location object

static getURLContent (url: str)

class geography.locator.**Locator** (db_file=None, correctMisspelling=False, debug=False)

Bases: object

location handling

cities_for_name (cityName)

find cities with the given cityName

Parameters **cityName** (string) – the potential name of a city

Returns a list of city records

correct_country_misspelling (name)

correct potential misspellings :param name: the name of the country potentially misspelled :type name: string

Returns correct name of unchanged

Return type string

createViews (sqlDB)

db_has_data()
check whether the database has data / is populated

Returns True if the cities table exists and has more than one record

Return type boolean

db_recordCount (tableList, tableName)
count the number of records for the given tableName

Parameters

- **tableList** (*list*) – the list of table to check
- **tableName** (*str*) – the name of the table to check

Returns int: the number of records found for the table

disambiguate (country, regions, cities, byPopulation=True)
try determining country, regions and city from the potential choices

Parameters

- **country** (*Country*) – a matching country found
- **regions** (*list*) – a list of matching Regions found
- **cities** (*list*) – a list of matching cities found

Returns the found city or None

Return type *City*

getAliases()
get the aliases hashTable

getCountry (name)
get the country for the given name :param name: the name of the country to lookup :type name: string

Returns the country if one was found or None if not

Return type *country*

getGeolite2Cities()
get the Geolite2 City-Locations as a list of Dicts

Returns a list of Geolite2 City-Locator dicts

Return type list

static getInstance (correctMisspelling=False, debug=False)
get the singleton instance of the Locator. If parameters are changed on further calls the initial parameters will still be in effect since the original instance will be returned!

Parameters

- **correctMisspelling** (*bool*) – if True correct typical misspellings
- **debug** (*bool*) – if True show debug information

getView()
get the view to be used

Returns the SQL view to be used for CityLookups e.g. GeoLite2CityLookup

Return type str

```
getWikidataCityPopulation (sqlDB, endpoint=None)

Parameters
    • sqlDB (SQLDB) – target SQL database
    • endpoint (str) – url of the wikidata endpoint or None if default should be used

static isISO (s)
    check if the given string is an ISO code

    Returns True if the string is an ISO Code

    Return type bool

is_a_country (name)
    check if the given string name is a country

    Parameters name (string) – the string to check
    Returns if pycountry thinks the string is a country

    Return type True

locateCity (places)
    locate a city, region country combination based on the given wordtoken information

    Parameters
        • places (list) – a list of places derived by splitting a locality e.g. “San Francisco, CA”
        • to "San Francisco", "CA" (leads) –

    Returns a city with country and region details

    Return type City

locator = None

places_by_name (placeName, columnName)
    get places by name and column :param placeName: the name of the place :type placeName: string :param columnName: the column to look at :type columnName: string

populateFromWikidata (sqlDB)
    populate countries and regions from Wikidata

    Parameters sqlDB (SQLDB) – target SQL database

populate_Cities (sqlDB)
    populate the given sqlDB with the Geolite2 Cities

    Parameters sqlDB (SQLDB) – the SQL database to use

populate_Cities_FromWikidata (sqlDB)
    populate the given sqlDB with the Wikidata Cities

    Parameters sqlDB (SQLDB) – target SQL database

populate_Countries (sqlDB)
    populate database with countries from wikiData

    Parameters sqlDB (SQLDB) – target SQL database

populate_Regions (sqlDB)
    populate database with regions from wikiData

    Parameters sqlDB (SQLDB) – target SQL database
```

```

populate_Version(sqlDB)
    populate the version table

    Parameters sqlDB (SQLDB) – target SQL database

populate_db(force=False)
    populate the cities SQL database which caches the information from the GeoLite2-City-Locations.csv file

    Parameters force (bool) – if True force a recreation of the database

readCSV(fileName)
recreateDatabase()
    recreate my lookup database

regions_for_name(region_name)
    get the regions for the given region_name (which might be an ISO code)

    Parameters region_name (string) – region name

    Returns the list of cities for this region

    Return type list

static resetInstance()

class geography.locator.Region(**kwargs)
    Bases: geography.locator.Location

    a Region (Subdivision)

country

static fromGeoLite2(record)
    create a region from a Geolite2 record

    Parameters record (dict) – the records as returned from a Query

    Returns the corresponding region information

    Return type Region

static fromWikidata(record)
    create a region from a Wikidata record

    Parameters record (dict) – the records as returned from a Query

    Returns the corresponding region information

    Return type Region

classmethod getSamples()

class geography.locator.RegionManager(name: str = 'RegionManager', primaryKey: str = None, config=None, handleInvalidListTypes=False, filterInvalidListTypes=False, debug=False)
    Bases: geography.locator.LocationManager

    a list of regions

classmethod fromJSONBackup(config: lodstorage.storageconfig.StorageConfig = None)
    get region list from json backup (json backup is based on wikidata query results)

    Returns RegionList based on the json backup

classmethod fromWikidata(config: lodstorage.storageconfig.StorageConfig = None)
    get region list form wikidata

```

```
classmethod from_sqlDb(sqlDB, config: lodstorage.storageconfig.StorageConfig = None)
classmethod getLocationLodFromJsonBackup()

geography.locator.main(argv=None)
    main program.
```

1.5 geography.places module

```
class geography.places.PlaceContext(place_names, setAll=True)
    Bases: geography.locator.Locator

    Adds context information to a place name

    get_region_names(country_name)

    setAll()
        Set all context information

    set_cities()
        set the cities information

    set_countries()
        get the country information from my places

    set_other()

    set_regions()
```

1.6 geography.prefixtree module

1.7 geography.utils module

```
geography.utils.fuzzy_match(s1, s2, max_dist=0.8)
    Fuzzy match the given two strings with the given maximum distance :param s1: string: First string :param s2: string: Second string :param max_dist: float: The distance - default: 0.8
```

Returns jellyfish jaro_winkler_similarity based on https://en.wikipedia.org/wiki/Jaro-Winkler_distance

Return type float

```
geography.utils.remove_non_ascii(s)
```

Remove non ascii chars from the given string :param s: string: The string to remove chars from

Returns The result string with non-ascii chars removed

Return type string

Hat tip: <http://stackoverflow.com/a/1342373/2367526>

1.8 geography.wikidata module

Created on 2020-09-23

@author: wf

```
class geography.wikidata.Wikidata(endpoint='https://query.wikidata.org/sparql')
Bases: object

Wikidata access

getCities(region=None, country=None)
    get the cities from Wikidata

    Parameters
        • region – List of countryWikiDataIDs. Limits the returned cities to the given countries
        • country – List of regionWikiDataIDs. Limits the returned cities to the given regions

getCitiesOfRegion(regionWikidataId: str, limit: int)
    Queries the cities of the given region. If the region is a city state the region is returned as city. The cities
    are ordered by population and can be limited by the given limit attribute.

    Parameters
        • regionWikidataId – wikidata id of the region the cities should be queried for
        • limit – Limits the amount of returned cities

    Returns Returns list of cities of the given region ordered by population

getCityPopulations(profile=True)
    get the city populations from Wikidata

    Parameters profile (bool) – if True show profiling information

static getCoordinateComponents(coordinate: str) -> (<class 'float'>, <class 'float'>)
    Converts the wikidata coordinate representation into its subcomponents longitude and latitude Example:
    ‘Point(-118.25 35.05694444)’ results in (-118.25 ‘35.05694444’)

    Parameters coordinate – coordinate value in the format as returned by wikidata queries

    Returns Returns the longitude and latitude of the given coordinate as separate values

getCountries()
    get a list of countries

    try query

getRegions()
    get Regions from Wikidata

    try query

static getValuesClause(varName: str, values, wikidataEntities: bool = True)
    generates the SPARQL value clause for the given variable name containing the given values :param var-
    Name: variable name for the ValuesClause :param values: values for the clause :param wikidataEntities:
    if true the wikidata prefix is added to the values otherwise it is expected taht the given values are proper
    IRIs :type wikidataEntities: bool

    Returns str

static getWikidataId(wikidataURL: str)
    Extracts the wikidata id from the given wikidata URL

    Parameters wikidataURL – wikidata URL the id should be extracted from

    Returns The wikidata id if present in the given wikidata URL otherwise None
```

1.9 Module contents

main geography 3 module

`geography.get_geoplace_context(url=None, text=None, debug=False)`

Get a place context for a given text with information about country, region, city and other based on NLTK Named Entities having the Geographic(GPE) label.

Parameters

- `url` (`String`) – the url to read text from (if any)
- `text` (`String`) – the text to analyze
- `debug` (`boolean`) – if True show debug information

Returns PlaceContext: the place context

Return type places

`geography.get_place_context(url=None, text=None, labels=['GPE', 'GSP', 'PERSON', 'ORGANIZATION'], debug=False)`

Get a place context for a given text with information about country, region, city and other based on NLTK Named Entities in the label set Geographic(GPE), Person(PERSON) and Organization(ORGANIZATION).

Parameters

- `url` (`String`) – the url to read text from (if any)
- `text` (`String`) – the text to analyze
- `debug` (`boolean`) – if True show debug information

Returns PlaceContext: the place context

Return type pc

`geography.locateCity(location, correctMisspelling=False, debug=False)`

locate the given location string :param location: the description of the location :type location: string

Returns the location

Return type Locator

CHAPTER 2

setup module

CHAPTER 3

tests package

3.1 Submodules

3.2 tests.test_extractor module

```
class tests.test_extractor.TestExtractor(methodName='runTest')
Bases: unittest.case.TestCase

test Extractor

check(places, expectedList)
    check the places for begin non empty and having at least the expected List of elements

Parameters
    • places (Places) – the places to check
    • expectedList (list) – the list of elements to check

setUp()
    Hook method for setting up the test fixture before exercising it.

tearDown()
    Hook method for deconstructing the test fixture after testing it.

testExtractorFromText()
    test different texts for getting geo context information

testExtractorFromUrl()
    test the extractor

testGeographyIssue32()
    test https://github.com/ushahidi/geography/issues/32

testGetGeoPlace()
    test geo place handling
```

```
testIssue10()
    test https://github.com/somnathrakshit/geography3/issues/10 Add ISO country code

testIssue7()
    test https://github.com/somnathrakshit/geography3/issues/7 disambiguating countries

testIssue9()
    test https://github.com/somnathrakshit/geography3/issues/9 [BUG]AttributeError: 'NoneType' object has
        no attribute 'name' on "Pristina, Kosovo"

testStackOverflow54721435()
    see https://stackoverflow.com/questions/54721435/unable-to-extract-city-names-from-a-text-using-geographypython

testStackoverflow43322567()
    see https://stackoverflow.com/questions/43322567

testStackoverflow54077973()
    see https://stackoverflow.com/questions/54077973/geography3-library-for-extracting-the-locations-in-the-text-gives-unicode

testStackoverflow54712198()
    see https://stackoverflow.com/questions/54712198/not-only-extracting-places-from-a-text-but-also-other-names-in-geograph

testStackoverflow55548116()
    see https://stackoverflow.com/questions/55548116/geography3-library-is-not-working-properly-and-give-traceback-error

testStackoverflow62152428()
    see https://stackoverflow.com/questions/62152428/extracting-country-information-from-description-using-geography?
    noredirect=1#comment112899776_62152428
```

3.3 tests.test_locator module

Created on 2020-09-19

@author: wf

```
class tests.test_locator.TestLocator(methodName='runTest')
Bases: unittest.case.TestCase

test the Locator class from the location module

checkExamples(examples, countries, debug=False, check=True)
    check that the given example give results in the given countries :param examples: a list of example location
    strings :type examples: list :param countries: a list of expected country iso codes :type countries: list

setUp()
    Hook method for setting up the test fixture before exercising it.

tearDown()
    Hook method for deconstructing the test fixture after testing it.

testDelimiters()
    test the delimiter statistics for names

testExamples()
    test examples

testGeolite2Cities()
    test the locs.db cache for cities

testHasData()
    check has data and populate functionality
```

```

testIsoRegexp()
    test regular expression for iso codes

testIssue15()
    https://github.com/somnathrakshit/geography3/issues/15 test Issue 15 Disambiguate via population, gdp
    data

testIssue17()
    test issue 17:
    https://github.com/somnathrakshit/geography3/issues/17
    [BUG] San Francisco, USA and Auckland, New Zealand should be locatable #17

testIssue19()
    test issue 19

testIssue22()
    https://github.com/somnathrakshit/geography3/issues/22

testIssue41_CountriesFromErdem()
    test getting Country list from Erdem

testIssue_42_distance()
    test haversine and location

testPopulation()
    test adding population data from wikidata to GeoLite2 information

testProceedingsExample()
    test a proceedings title Example

testStackOverflow64379688()
    compare old and new geography interface

testStackOverflow64418919()
    https://stackoverflow.com/questions/64418919/problem-retrieving-region-in-us-with-geography3

testWordCount()
    test the word count

```

3.4 tests.test_places module

```

class tests.test_places.TestPlaces (methodName='runTest')
Bases: unittest.case.TestCase

test Places

setUp()
    Hook method for setting up the test fixture before exercising it.

tearDown()
    Hook method for deconstructing the test fixture after testing it.

testPlaces()
    test places

```

3.5 tests.test_prefixtree module

3.6 tests.test_wikidata module

Created on 2020-09-23

@author: wf

```
class tests.test_wikidata.TestWikidata(methodName='runTest')
    Bases: unittest.case.TestCase

    test the wikidata access for cities

    setUp()
        Hook method for setting up the test fixture before exercising it.

    tearDown()
        Hook method for deconstructing the test fixture after testing it.

    testGetCitiesOfRegion()
        Test getting cities based on region wikidata id

    testGetCoordinateComponents()
        test the splitting of coordinate components in WikiData query results

    testGetWikidataId()
        test getting a wikiDataId from a given URL

    testLocatorWithWikiData()
        test Locator

    testWikidataCities()
        test getting city information from wikidata
        1372 Singapore 749 Beijing, China 704 Paris, France 649 Barcelona, Spain 625 Rome, Italy 616 Hong
        Kong 575 Bangkok, Thailand 502 Vienna, Austria 497 Athens, Greece 483 Shanghai, China

    testWikidataCountries()
        test getting country information from wikidata
```

3.7 Module contents

CHAPTER 4

Indices and tables

- genindex
- modindex
- search

Python Module Index

g

geography, 12
geography.extraction, 1
geography.labels, 1
geography.locator, 2
geography.places, 10
geography.utils, 10
geography.wikidata, 10

t

tests, 18
tests.test_extractor, 15
tests.test_locator, 16
tests.test_places, 17
tests.test_wikidata, 18

Index

B

balltreeQueryResultToLocationManager() (*geography.locator.Location method*), 4

C

check() (*tests.test_extractor.TestExtractor method*), 15
checkExamples() (*tests.test_locator.TestLocator method*), 16
cities (*geography.locator.LocationContext attribute*), 5
cities_for_name() (*geography.locator.Locator method*), 6
City (*class in geography.locator*), 2
CityManager (*class in geography.locator*), 2
correct_country_misspelling() (*geography.locator.Locator method*), 6
countries (*geography.locator.LocationContext attribute*), 5
Country (*class in geography.locator*), 3
country (*geography.locator.City attribute*), 2
country (*geography.locator.Region attribute*), 9
CountryManager (*class in geography.locator*), 3
createViews() (*geography.locator.Locator method*), 6

D

db_has_data() (*geography.locator.Locator method*), 6
db_recordCount() (*geography.locator.Locator method*), 7
default (*geography.labels.Labels attribute*), 2
disambiguate() (*geography.locator.Locator method*), 7
distance() (*geography.locator.Location method*), 4
downloadBackupFile() (*geography.locator.LocationManager method*), static 5

E

Earth (*class in geography.locator*), 4
Extractor (*class in geography.extraction*), 1

F

find_entities() (*geography.extraction.Extractor method*), 1
find_geoEntities() (*geography.extraction.Extractor method*), 1
from_sqlDb() (*geography.locator.CountryManager class method*), 4
from_sqlDb() (*geography.locator.RegionManager class method*), 9
fromCache() (*geography.locator.LocationContext class method*), 5
fromErdem() (*geography.locator.CountryManager class method*), 3
fromGeoLite2() (*geography.locator.City static method*), 2
fromGeoLite2() (*geography.locator.Country static method*), 3
fromGeoLite2() (*geography.locator.Region static method*), 9
fromJSONBackup() (*geography.locator.CityManager class method*), 2
fromJSONBackup() (*geography.locator.CountryManager class method*), 3
fromJSONBackup() (*geography.locator.LocationContext class method*), 5
fromJSONBackup() (*geography.locator.RegionManager class method*), 9
fromPyCountry() (*geography.locator.Country static method*), 3
fromWikidata() (*geography.locator.CityManager class method*), 3
fromWikidata() (*geography.locator.CountryManager class method*), 3
fromWikidata() (*geography.locator.Region static method*), 9
fromWikidata() (*geography.locator.RegionManager*)

class method), 9
fuzzy_match () (*in module geography.utils*), 10

G

geo (*geography.labels.Labels attribute*), 2
geography (*module*), 12
geography.extraction (*module*), 1
geography.labels (*module*), 1
geography.locator (*module*), 2
geography.places (*module*), 10
geography.utils (*module*), 10
geography.wikidata (*module*), 10
get_geoPlace_context () (*in module geography*), 12
get_place_context () (*in module geography*), 12
get_region_names () (*geography.places.PlaceContext method*), 10
getAliases () (*geography.locator.Locator method*), 7
getBackupDirectory () (*geography.locator.LocationManager method*), 6
getBallTuple () (*geography.locator.LocationManager method*), 6
getByName () (*geography.locator.LocationManager method*), 6
getCities () (*geography.locator.LocationContext method*), 5
getCities () (*geography.wikidata.Wikidata method*), 11
getCitiesOfRegion () (*geography.wikidata.Wikidata method*), 11
getCityPopulations () (*geography.wikidata.Wikidata method*), 11
getCoordinateComponents () (*geography.wikidata.Wikidata static method*), 11
getCountries () (*geography.locator.LocationContext method*), 5
getCountries () (*geography.wikidata.Wikidata method*), 11
getCountry () (*geography.locator.Locator method*), 7
getDefaultConfig () (*geography.locator.LocationContext static method*), 5
getFileContent () (*geography.locator.LocationManager static method*), 6
getGeolite2Cities () (*geography.locator.Locator method*), 7
getInstance () (*geography.locator.Locator static method*), 7
getLocationByID () (*geography.locator.LocationManager method*),

6
getLocationLodFromJsonBackup () (*geography.locator.CityManager class method*), 3
getLocationLodFromJsonBackup () (*geography.locator.CountryManager class method*), 4
getLocationLodFromJsonBackup () (*geography.locator.RegionManager class method*), 10
getLocationsWithinRadius () (*geography.locator.Location method*), 4
getNClosestLocations () (*geography.locator.Location method*), 4
getRegions () (*geography.locator.LocationContext method*), 5
getRegions () (*geography.wikidata.Wikidata method*), 11
getSamples () (*geography.locator.City class method*), 2
getSamples () (*geography.locator.Country class method*), 3
getSamples () (*geography.locator.Location class method*), 4
getSamples () (*geography.locator.Region class method*), 9
getURLContent () (*geography.locator.LocationManager static method*), 6
getValuesClause () (*geography.wikidata.Wikidata static method*), 11
getView () (*geography.locator.Locator method*), 7
getWikidataCityPopulation () (*geography.locator.Locator method*), 7
getWikidataId () (*geography.wikidata.Wikidata static method*), 11

H

haversine () (*geography.locator.Location static method*), 5

I

interlinkLocations () (*geography.locator.LocationContext method*), 5
is_a_country () (*geography.locator.Locator method*), 8
isISO () (*geography.locator.Locator static method*), 8
isKnownAs () (*geography.locator.Location method*), 5

L

Labels (*class in geography.labels*), 2
locateCity () (*geography.locator.Locator method*), 8
locateCity () (*in module geography*), 12

locateLocation() (geography.locator.LocationContext method), 5
L
 Location (*class in geography.locator*), 4
 LocationContext (*class in geography.locator*), 5
 LocationManager (*class in geography.locator*), 5
 Locator (*class in geography.locator*), 6
 locator (*geography.locator.Locator attribute*), 8

M
 main () (*in module geography.locator*), 10

P
 PlaceContext (*class in geography.places*), 10
 places_by_name () (geography.locator.Locator method), 8
 populate_Cities () (geography.locator.Locator method), 8
 populate_Cities_FromWikidata () (geography.locator.Locator method), 8
 populate_Countries () (geography.locator.Locator method), 8
 populate_db () (geography.locator.Locator method), 9
 populate_Regions () (geography.locator.Locator method), 8
 populate_Version () (geography.locator.Locator method), 8
 populateFromWikidata () (geography.locator.Locator method), 8

R
 radius (*geography.locator.Earth attribute*), 4
 readCSV () (geography.locator.Locator method), 9
 recreateDatabase () (geography.locator.Locator method), 9
 Region (*class in geography.locator*), 9
 region (*geography.locator.City attribute*), 2
 RegionManager (*class in geography.locator*), 9
 regions (*geography.locator.LocationContext attribute*), 5
 regions_for_name () (geography.locator.Locator method), 9
 remove_non_ascii () (*in module geography.utils*), 10
 resetInstance () (geography.locator.Locator static method), 9

S
 set_cities () (geography.places.PlaceContext method), 10
 set_countries () (geography.places.PlaceContext method), 10
 set_other () (geography.places.PlaceContext method), 10
 set_regions () (geography.places.PlaceContext method), 10
 set_text () (geography.extraction.Extractor method), 1
 setAll () (geography.places.PlaceContext method), 10
 setUp () (tests.test_extractor.TestExtractor method), 15
 setUp () (tests.test_locator.TestLocator method), 16
 setUp () (tests.test_places.TestPlaces method), 17
 setUp () (tests.test_wikidata.TestWikidata method), 18
 setValue () (geography.locator.City method), 2
 split () (geography.extraction.Extractor method), 1

T
 tearDown () (tests.test_extractor.TestExtractor method), 15
 tearDown () (tests.test_locator.TestLocator method), 16
 tearDown () (tests.test_places.TestPlaces method), 17
 tearDown () (tests.test_wikidata.TestWikidata method), 18
 testDelimiters () (tests.test_locator.TestLocator method), 16
 testExamples () (tests.test_locator.TestLocator method), 16
 TestExtractor (*class in tests.test_extractor*), 15
 testExtractorFromText () (tests.test_extractor.TestExtractor method), 15
 testExtractorFromUrl () (tests.test_extractor.TestExtractor method), 15
 testGeographyIssue32 () (tests.test_extractor.TestExtractor method), 15
 testGeolite2Cities () (tests.test_locator.TestLocator method), 16
 testGetCitiesOfRegion () (tests.test_wikidata.TestWikidata method), 18
 testGetCoordinateComponents () (tests.test_wikidata.TestWikidata method), 18
 testGetGeoPlace () (tests.test_extractor.TestExtractor method), 15
 testGetWikidataId () (tests.test_wikidata.TestWikidata method), 18
 testHasData () (tests.test_locator.TestLocator method), 16
 testIsoRegexp () (tests.test_locator.TestLocator method), 16
 testIssue10 () (tests.test_extractor.TestExtractor method), 15

testIssue15 () *(tests.test_locator.TestLocator method)*, 17
testIssue17 () *(tests.test_locator.TestLocator method)*, 17
testIssue19 () *(tests.test_locator.TestLocator method)*, 17
testIssue22 () *(tests.test_locator.TestLocator method)*, 17
testIssue41_CountriesFromErdem () *(tests.test_locator.TestLocator method)*, 17
testIssue7 () *(tests.test_extractor.TestExtractor method)*, 16
testIssue9 () *(tests.test_extractor.TestExtractor method)*, 16
testIssue_42_distance () *(tests.test_locator.TestLocator method)*, 17
TestLocator (*class in tests.test_locator*), 16
testLocatorWithWikiData () *(tests.test_wikidata.TestWikidata method)*, 18
TestPlaces (*class in tests.test_places*), 17
testPlaces () *(tests.test_places.TestPlaces method)*, 17
testPopulation () *(tests.test_locator.TestLocator method)*, 17
testProceedingsExample () *(tests.test_locator.TestLocator method)*, 17
tests (*module*), 18
tests.test_extractor (*module*), 15
tests.test_locator (*module*), 16
tests.test_places (*module*), 17
tests.test_wikidata (*module*), 18
testStackoverflow43322567 () *(tests.test_extractor.TestExtractor method)*, 16
testStackoverflow54077973 () *(tests.test_extractor.TestExtractor method)*, 16
testStackoverflow54712198 () *(tests.test_extractor.TestExtractor method)*, 16
testStackOverflow54721435 () *(tests.test_extractor.TestExtractor method)*, 16
testStackoverflow55548116 () *(tests.test_extractor.TestExtractor method)*, 16
testStackoverflow62152428 () *(tests.test_extractor.TestExtractor method)*, 16
testStackOverflow64379688 () *(tests.test_locator.TestLocator method)*, 17
testStackOverflow64418919 () *(tests.test_locator.TestLocator method)*, 17

U

updateCity () *(geography.locator.CityManager method)*, 3

W

Wikidata (*class in geography.wikidata*), 10